

Name: _____ **Date:** _____

Fall Prevention Pre Test

1. **The most common causes of injury on a construction site are _____**
 - A. Fires
 - B. Injuries from falling objects
 - C. Falls
 - D. Faulty equipment

2. **The ultimate responsibility for on-the-job safety rests with _____**
 - A. You
 - B. Your supervisor
 - C. Human resources
 - D. OSHA

3. **A type 1A ladder is rated for _____ use.**
 - A. 200 pounds, light duty/household
 - B. 225 pounds, medium duty/commercial
 - C. 250 pounds, heavy duty/industrial
 - D. 300 pounds, extra heavy duty/professional

4. **If you are going to step onto a platform or roof, the top of the ladder should extend at least _____ feet above the point where the ladder touches the upper landing surface.**
 - A. 2
 - B. 3
 - C. 4
 - D. 5

5. **You should report an accident immediately after it occurs so that _____**
 - A. Someone else can use the machine
 - B. First-aid can be applied if necessary
 - C. Everyone else can see what's going on
 - D. Your supervisor can hide the evidence

6. **If an employee falls into their fall protection equipment what should happen to the equipment.**
 - A. Inspect it and return to service if it is in good condition
 - B. Take it out of service immediately
 - C. If the employee was not injured cut it up and throw it away
 - D. Save the equipment and only use it when you think someone might fall. It worked the first time so it should work the second time.

7. **An anchorage point for a Fall RESTRAINT system must be capable of supporting?**
 - A. 5,000 pounds
 - B. 1,500 pounds
 - C. 12,000 pounds
 - D. 3,000 pounds

Name: _____ **Date:** _____

Fall Prevention Pre Test

- 8. A floor hole wider than _____ must be protected.**
- A. 12 inches
 - B. 24 inches
 - C. 2 inches
 - D. 19 inches
- 9. When fall arrest equipment is used, employers must assure that _____.**
- A. All equipment is properly inspected before each use
 - B. Users have calculated total fall distance
 - C. A rescue plan is in place to rescue a fallen employee
 - D. All of the above
- 10. A fall arrest system is required when a worker is operating at a height of ?**
- A. 3 feet or more
 - B. 6 feet or more
 - C. 10 feet or more
 - D. None of the above
- 11. Who is primarily responsible for providing employees with a fall protection system?**
- A. The manufacturer of the fall protection system
 - B. The employer
 - C. The employee
 - D. The insurer
- 12. When should ladders be inspected?**
- A. Each day before use
 - B. At least once a week
 - C. At least once a month
 - D. At least once a year
- 13. At what height do open-sided floors in construction require guardrails?**
- A. 1 foot
 - B. 2 feet
 - C. 4 feet
 - D. 6 feet
- 14. What items and/or elements and/or approaches can be legally and safely used to help prevent falls during roof construction activities:**
- A. Guardrails
 - B. Covering holes and openings with sheathing
 - C. Ensuring workers are properly and adequately trained
 - D. All of the above
- 15. Inspections of scaffolds must be conducted?**
- A. By a competent person
 - B. Before each work shift
 - C. After scaffold is erected or modified
 - D. All of the above